

2fw

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Serial No.: 10/617,717

Atty. Docket No: 1507 US

Filed: 07/14/2003

Confirmation No: 4193

Group Art Unit: 2832

Applicant: Antony Howell

Title: Magnetically operated hinge switch

CERTIFICATE OF MAILING (37 CFR 1.8a)

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown with sufficient postage as First Class Mail in an envelope addressed to the: Commissioner for Patents, P.P. Box 1450, Alexandria, VA 22313-1450.

06/17/2004  
Date of Signature  
and Mail Deposit

By: Lonnie R. Drayer  
Lonnie R. Drayer  
Registration No. 30,375  
Attorney for Applicant(s)

Commissioner for Patents  
Alexandria, VA 22313-1450

SUBMISSION OF PRIORITY DOCUMENT

Submitted herewith is a certified copy of Great Britain Patent Application 0308620.4, filed 14 April 2003, for which applicant has made a claim of foreign priority in the subject application.

Respectfully submitted,

Lonnie R. Drayer  
Lonnie R. Drayer  
Registration No. 30,375  
Attorney for Applicant(s)

Key Safety Systems, Inc.  
5300 Allen K Breed Hwy  
Lakeland, Florida 33811-1130  
Phone (863) 668-6707  
Fax (863) 668-6130

**THIS PAGE BLANK (USPTO)**



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 23 July 2003

**THIS PAGE BLANK (USPTO)**


# The Patent Office

15APR03 E800258-1 001038  
P01/7700 0.00-0308620.4

1/77

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference	DC.P304398GB/5662		
2. Patent application number (The Patent Office will fill in this part)	0308620.4		
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Breed Automotive Technology Inc 5300 Allen K Breed Highway PO Box 33050 Lakeland Florida 33807-3050 United States of America		
Patents ADP number (if you know it)	8610529001		
If the applicant is a corporate body, give the country/state of its incorporation	United States of America - DELAWARE (see A1/d/d 9/5/03)		
4. Title of the invention	Magnetically Operated Hinge Switch		
5. Name of your agent (if you have one)	WITHERS & ROGERS		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Goldings House 2 Hays Lane London SE1 2HW		
Patents ADP number (if you know it)	1776001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
	/	/	/
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
	/	/	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

**Patents Form 1/77**


9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form /

Description 5

Claim(s) 4

Abstract 1

Drawing (s) 1 + 1 

10. If you are also filing any of the following, state how many against each item.

Priority documents /

Translations of priority documents /

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 1

Any other documents /  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature Wilfred Rogers Date 14/04/03

12. Name and daytime telephone number of person to contact in the United Kingdom

Dave Croston

0121 245 3900

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

P304390GB

**MAGNETICALLY OPERATED HINGE SWITCH**

The present invention relates to switches used to detect the closing of a door or lid where two parts of the switch connected by a hinge are moved towards each other.

In many applications it is desirable to be able to positively detect that a certain action has taken place, for example that the hood of a car has been properly closed. Prior art devices are usually comprised of a base that contains a sensor and an arm that is mounted by a hinge to the base that contains a means for interacting with the sensor. These prior art devices typically require three or more separate parts and a metal biasing means for keeping the sensor open. The metal biasing means can often be exposed to corrosion depending on the environment of the use. What is needed is a hinge type switch of simpler and more robust construction.

The hinge switch of this invention has a unitary plastic body that can be formed by injection moulding or extrusion. The unitary plastic body has a base that can be fastened to a support structure by a plurality of fasteners that pass through the base and through the support structure. The base is connected to an arm by an elastic U-shaped portion of the plastic body that acts as both a hinge and a biasing member. The U-shaped portion is substantially thinner and thus more flexible than the base or the arm. The base has an end

face into which is formed a sensor-receiving cavity. Positioned within the cavity is a sensor module that is connected by wire leads to a connector plug. The sensor module contains a magnetic field sensor such as a reed switch or Hall effect sensor. The arm is less wide than the base so that it does not block access to the plurality of fasteners that mount to the base to the support structure. The arm has portions defining an opening into which an activation magnet is placed.

It is a feature of the present invention to provide a switch of unitary construction.

Is a further feature of the present invention to provide a hinge switch wherein the material of the hinge elastically biases the switch to an open position.

It is another feature of the present invention to provide a hinge switch that is not subject to corrosion.

Further features and advantages of the invention will be apparent from the following detailed description when taken in conjunction with the accompanying drawings.

FIG. 1 is an exploded isometric view of the lever arm sensor of this invention.



FIG. 2 is a side elevational view partially cut away in section, of the lever arm sensor of FIG. 1.

Referring more particularly to FIGS. 1-2 wherein like numbers refer to similar parts, a lever arm switch 20 is shown in FIGS. 1 and 2. The lever arm switch 20 has a plastic body 21 which includes a base 22, a hinge 24, and a closure arm 26 which are integrally formed of plastic, for example polypropylene, as a single injection moulded piece. The hinge 24 takes on a smooth U-shaped form 28 as illustrated in FIG. 2 when the closure arm 26 is brought into engagement with a stop 30 which is integral with the base 22 and the entire switch 20.

The base 22 has two mounting holes 32 into which fasteners 34 are positioned to hold the base 22 fixed with respect to a mounting structure 36 by passing through the holes 32 in the base and into corresponding holes 37 in the mounting structure. The base 22 has a thick section 38 that is joined by a smooth transitional section 40 to the hinge 24. The mounting holes 32 pass vertically downwardly through the thick section 38 of the base. The base 22 has an overall rectangular shape with an end face 42 opposite the hinge 24 into which is formed a sensor cavity 44. The stop 30 is positioned above the sensor cavity 44.

A sensor module 46 is positioned within the sensor cavity 44. The sensor module 46 contains a magnetic field sensor 48 which may be a reed switch, a Hall effect sensor, a GMR sensor, an induction coil or other means of detecting an electromagnetic field. The sensor is connected to a two or more wire leads 49 that terminate in a connector plug 52.

The closure arm 26 is connected to an upper transition section 50 but does not extend along the entire transition section 50 so that the arm 26 does not overlie the mounting holes 32 in the base 22 allowing access to install or remove the fasteners 34. Thus the arm 26 and the transition section 50 define a rectangular open space 54 which allows vertical access to the mounting fasteners 34. The closure arm 26 has portions defining a cavity 56 into which in activation magnet 58 is bonded or insertion moulded. The magnet 58 is positioned so as to activate, or be detected by the magnetic field sensor 48 within the sensor module 46 positioned within the sensor cavity 44 within the base 22. The stop 30 limits the motion of the closure arm 26, as shown in FIG. 2 and positions the activation magnet 58 to be detected by the magnetic field sensor 48 within the sensor module 46 which is mounted in the sensor cavity 44.

The closure arm 26 and the base 22 are about the same thickness, and are connected by the lower transition section 40 and the upper transition section 50 to the hinge 24 which

has about one-half the thickness of the closure arm 26 and the base 22. The greater thickness of the base 22 and the closure arm 26 means that substantially all elastic deformation caused by the motion of the closure arm downwardly, as indicated by arrow 60, occurs in the hinge 24. The smooth transition sections 40, 50 provide a gradual transition between the flexible hinge 24 and the substantially rigid base 22 and closure arm 26. The gradual transition prevents stress concentrations caused by the change in section between the base 22 and the arm 26 and the hinge 24. The minimization of stress concentrations results in a relatively low stressed hinge 24 with a flexure of about 30 degrees or less and the use of a suitable plastic such as polypropylene will produce a switch with a desirable long life.

It should be understood that while the hinge switch 20 is preferably formed as a single injection moulded part it could be cut from a continuous extrusion. It should also be understood that the activation magnet 58 and the sensor module 46 could be mounted to the hinge switch 20 by moulding-in-place, bonding, or by being potted, heat staked or fastened to the switch body 21. It should also be understood that if a reed switch is used as the magnetic field sensor, it could be of the type that is normally open, or the type which is normally closed. Without thickness discontinuity, should be understood to mean a gradual, smooth transition to avoid producing a stress concentration.

**CLAIMS:-****1. A switch comprising:**

a single piece plastic hinge, the hinge having a base portion and flexible section which extends between the base portion and an arm portion extending over the base portion;

a magnetic field sensor mounted to the base portion; and

an activation magnet mounted to the arm portion, the flexible section elastically biasing the arm portion and the actuation magnet away from magnetic a field sensor mounted to the base portion so that the magnetic field sensor is activated by elastically pushing the arm portion towards the base portion.

2. The switch of claim 1 wherein the base portion has portions forming a stop which extends upwardly from the base portion, and which engages the arm when it is moved downwardly towards the base, thus limiting the travel of the arm towards the base.

3. The switch of claim 1 wherein the base portion transitions without thickness discontinuity into the hinge portion which is approximately one-half as thick as the base

portion, and the hinge portion transitions without thickness discontinuity into the arm portion which is about as thick as the base portion.

4. The switch of claim 1 wherein the base portion has at least one fastener hole, and wherein the arm portion does not extend over the at least one fastener hole.

5. The switch of claim 1 wherein the magnetic field sensor is a Hall effect sensor.

6. The switch of claim 1 wherein the magnetic field sensor is a reed switch.

7. The switch of claim 1 wherein portions of the arm portion form a magnet receiving cavity in which the activation magnet is positioned.

8. The switch of claim 1 wherein the plastic hinge is constructed of polypropylene.

9. A switch comprising:

a single piece plastic hinge body;

a base forming a portion of the plastic hinge body, the base being mounted to a support structure by a plurality of fasteners extending through the base;

a U-shaped hinge integrally formed with the base;

an arm integrally formed with the base and the U-shaped hinge, wherein the U-shaped hinge extends between the base and the arm, and wherein the arm extends over at least a portion of the base;

a magnetic field sensor mounted to the base; and

an activation magnet mounted to the arm, the U-shaped hinge elastically biasing the arm portion and the activation magnet away from the magnetic field sensor mounted to the base so that the magnetic field sensor is activated by elastically pushing the arm portion towards the base.

10. The switch of claim 9 wherein the base has portions forming a stop which extends upwardly from the base, towards the arm, and which engages the arm when it is moved downwardly towards the base, the stop limiting the travel on the arm towards the base.

11. The switch of claim 9 wherein the base transitions without thickness discontinuity into the U-shaped hinge which is substantially less thick than the base, and the U-shaped hinge transitions without thickness discontinuity into the arm portion which is about as thick as the base.

12. The switch of claim 9 wherein the base has portions defining at least one fastener hole, and wherein the arm does not extend over the at least one fastener hole.
13. The switch of claim 9 wherein the base has an end face opposite the U-shaped hinge, and wherein portions of the base form a sensor cavity into which the magnetic field sensor is placed.
14. The switch of claim 9 wherein the magnetic field sensor is a Hall effect sensor.
15. The switch of claim 9 wherein the magnetic field sensor is a reed switch.
16. The switch of claim 9 wherein portions of the arm form a magnet receiving cavity in which the activation magnet is positioned.
17. The switch of claim 9 wherein the extruded plastic hinge body is constructed of polypropylene.
18. A switch substantially as here in before described with reference to figures 1 and 2 of the accompanying drawings.


**THIS PAGE BLANK (USPTO)**



**ABSTRACT****MAGNETICALLY OPERATED HINGE SWITCH**

A switch has a unitary plastic body that can be formed by injection moulding or extrusion. The body has a base that holds a magnetic field sensor. The base is fastened to a support structure by a plurality of fasteners. The base is connected to an arm by an elastic U-shaped portion of the plastic body that acts as both a hinge and a biasing member. The arm positions an activation magnet over the base and the sensor. The arm does not block access to fasteners that mount the switch to the support structure.

**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**